

Barrel 200

Barrel

DHW boiler with internal treatment and increased coil



TECHNICAL FEATURES

- Water-heater made of high quality steel with 1 fixed pipe-coil, complete with anodic protection, inside treatment according to norm DIN 4753 and UNI 10025. Insulation: Foamed hard polyurethane layer 50 mm (mod.200÷500), soft polyurethane 100 mm (mod. 800÷1000).

To be integrated on all kind of plants.
Storage rapidity, abundant and continuous erogation.
High efficiency for low exercise costs.
Absolute hygiene.
Long durability without corrosion.
Simplicity of installation.
Efficient heat-exchange surface.

- "S" version equipped with double heat exchanger coil

Technical sheet

Description	Unit of measurement	Value
Maximum overturning height	-	1375
Tank capacity	L	212
Height	mm	1215
Insulation tickness	mm	50

ADVANTIX SPA

Via San Giuseppe Lavoratore, 24 – Loc. La Macia Z.A.I – 37040 ARCOLE (Verona)

Tel. 0039-0457636585 – 0457636591 – Fax 0039-0457636551

C.F.e P.IVA 01209000239 – Iscritta presso il Tribunale di Verona ai n° 12621/17484 – Capitale Sociale 3.100.000 € i.v.

**AZIENDA CON SISTEMA
DI GESTIONE QUALITÀ
CERTIFICATO DA DNV GL
= ISO 9001 =**

Barrel 200

Barrel

DHW boiler with internal treatment and increased coil



Offer Number: 21708

Date: 04/28/2021

Loose accessories

RE2.0M3 - 2 kW single phase electric heater

VAS - Mixing safety valve

VE24AT - 24 liters expansion vassel

ADVANTIX SPA

Via San Giuseppe Lavoratore, 24 – Loc. La Macia Z.A.I – 37040 ARCOLE (Verona)

Tel. 0039-0457636585 – 0457636591 – Fax 0039-0457636551

C.F.e P.IVA 01209000239 – Iscritta presso il Tribunale di Verona ai n° 12621/17484 – Capitale Sociale 3.100.000 € i.v.

Maxa Selection Software - 1.0.20.3

**AZIENDA CON SISTEMA
DI GESTIONE QUALITÀ
CERTIFICATO DA DNV GL
= ISO 9001 =**

Print date: 04/28/2021 11:19:13